



Water flowing through a traditional channel system (acequia) towards almond terraces (Joris de Vente)

Water harvesting from concentrated runoff for irrigation purposes ()

Boqueras (Spanish)


Water harvesting from intermittent streams towards nearby fields and terraces during runoff events.

Water shortage is one of the most limiting factors for sustainable agriculture in large parts of SE-Spain. Part of the solution of this problem may come from the restoration of traditional water harvesting structures. Many of these structures were widely used in SE-Spain already during Arab and Roman times, and are also widespread in N-Africa and the Middle East. However, nowadays in Spain many of them are abandoned and forgotten. Here, we describe the technology of a small earthen- or stone- built bund that diverts flood water from intermittent streams towards cultivated fields with almond orchards and/or cereals. The diverted water will temporarily flood the fields and provide the crops with water. Depending on the slope gradient and the amount of water to be harvested, the fields are organised as single terraces, or as a staircase of terraces. On fields with gradients above ~3%, terraces are necessary to reduce the gradient and to retain the floodwater as long as possible. Water is diverted from one terrace to the next through small spillways in the terrace. The spillways can best be fortified with stones to prevent bank gully formation. The extra input of surface water can double the almond yield. The use of these water harvesting structures is only possible under certain environmental and topographic conditions. The cultivated fields should be at a relatively short distance from an intermittent stream (<~50m), and the stream should have a sufficiently large upstream contributing area to provide significant amounts of runoff water during rainfall events. With these systems, water can be harvested up to 8 times per year, mostly in spring and autumn during high intensity rainfall events. A well designed Boquera system may provide up to 550 mm of additional water, in areas with an average annual rainfall of 300 mm.

Purpose of the Technology: The goal of this technology is to increase crop yield. In addition, these structures help to reduce the intensity of floods and reduce the damage caused by them by reducing runoff volume in intermittent streams.



Establishment / maintenance activities and inputs: Water harvesting requires the identification of a suitable location for the construction of a diversion structure. This requires assessment of expected water inflow, which can usually be based on simple field observation during rainfall events and based on local knowledge of land users. It is, however, important to consider whether there are activities upstream that possibly affect the water quality (e.g. farm animals) and to assess the implications the water harvesting might have downstream. Permission is required from the water authorities to construct any type of water harvesting structure. Such structures are built by creating a small bund (<1m height) in the centre or to the side of a stream. Depending on the size, the bund can be built with a shovel or a tractor. The water harvesting structure will require control and some maintenance after each important runoff event. When strengthened with concrete, maintenance will be reduced to approximately once every 5 years.

Natural / human environment: Soils are mostly of shallow to medium depth (20-60 cm), and slopes are gentle to moderate (5-15%). The climate is semi-arid with a mean annual rainfall around 300 mm. Droughts, centred in summer commonly last for more than 4-5 months. Annual potential evapotranspiration rates larger than 1000 mm are common.



: Guadalentin catchment, Murcia,

		:
• -1.7076, 37.7931		
		:
2 (10))	(approx. < 0.1
		?:
()	:	50
✓		(> 50)
		/



1. **Introduction**
 2. **Background**
 3. **Methodology**
 4. **Results**
 5. **Discussion**
 6. **Conclusion**
 7. **References**
 8. **Appendix**
 9. **Figure 1**
 10. **Figure 2**
 11. **Figure 3**
 12. **Figure 4**
 13. **Figure 5**
 14. **Figure 6**
 15. **Figure 7**
 16. **Figure 8**
 17. **Figure 9**
 18. **Figure 10**
 19. **Figure 11**
 20. **Figure 12**
 21. **Figure 13**
 22. **Figure 14**
 23. **Figure 15**
 24. **Figure 16**
 25. **Figure 17**
 26. **Figure 18**
 27. **Figure 19**
 28. **Figure 20**
 29. **Figure 21**
 30. **Figure 22**
 31. **Figure 23**
 32. **Figure 24**
 33. **Figure 25**
 34. **Figure 26**
 35. **Figure 27**
 36. **Figure 28**
 37. **Figure 29**
 38. **Figure 30**
 39. **Figure 31**
 40. **Figure 32**
 41. **Figure 33**
 42. **Figure 34**
 43. **Figure 35**
 44. **Figure 36**
 45. **Figure 37**
 46. **Figure 38**
 47. **Figure 39**
 48. **Figure 40**
 49. **Figure 41**
 50. **Figure 42**
 51. **Figure 43**
 52. **Figure 44**
 53. **Figure 45**
 54. **Figure 46**
 55. **Figure 47**
 56. **Figure 48**
 57. **Figure 49**
 58. **Figure 50**
 59. **Figure 51**
 60. **Figure 52**
 61. **Figure 53**
 62. **Figure 54**
 63. **Figure 55**
 64. **Figure 56**
 65. **Figure 57**
 66. **Figure 58**
 67. **Figure 59**
 68. **Figure 60**
 69. **Figure 61**
 70. **Figure 62**
 71. **Figure 63**
 72. **Figure 64**
 73. **Figure 65**
 74. **Figure 66**
 75. **Figure 67**
 76. **Figure 68**
 77. **Figure 69**
 78. **Figure 70**
 79. **Figure 71**
 80. **Figure 72**
 81. **Figure 73**
 82. **Figure 74**
 83. **Figure 75**
 84. **Figure 76**
 85. **Figure 77**
 86. **Figure 78**
 87. **Figure 79**
 88. **Figure 80**
 89. **Figure 81**
 90. **Figure 82**
 91. **Figure 83**
 92. **Figure 84**
 93. **Figure 85**
 94. **Figure 86**
 95. **Figure 87**
 96. **Figure 88**
 97. **Figure 89**
 98. **Figure 90**
 99. **Figure 91**
 100. **Figure 92**
 101. **Figure 93**
 102. **Figure 94**
 103. **Figure 95**
 104. **Figure 96**
 105. **Figure 97**
 106. **Figure 98**
 107. **Figure 99**
 108. **Figure 100**
 109. **Figure 101**
 110. **Figure 102**
 111. **Figure 103**
 112. **Figure 104**
 113. **Figure 105**
 114. **Figure 106**
 115. **Figure 107**
 116. **Figure 108**
 117. **Figure 109**
 118. **Figure 110**
 119. **Figure 111**
 120. **Figure 112**
 121. **Figure 113**
 122. **Figure 114**
 123. **Figure 115**
 124. **Figure 116**
 125. **Figure 117**
 126. **Figure 118**
 127. **Figure 119**
 128. **Figure 120**
 129. **Figure 121**
 130. **Figure 122**
 131. **Figure 123**
 132. **Figure 124**
 133. **Figure 125**
 134. **Figure 126**
 135. **Figure 127**
 136. **Figure 128**
 137. **Figure 129**
 138. **Figure 130**
 139. **Figure 131**
 140. **Figure 132**
 141. **Figure 133**
 142. **Figure 134**
 143. **Figure 135**
 144. **Figure 136**
 145. **Figure 137**
 146. **Figure 138**
 147. **Figure 139**
 148. **Figure 140**
 149. **Figure 141**
 150. **Figure 142**
 151. **Figure 143**
 152. **Figure 144**
 153. **Figure 145**
 154. **Figure 146**
 155. **Figure 147**
 156. **Figure 148**
 157. **Figure 149**
 158. **Figure 150**
 159. **Figure 151**
 160. **Figure 152**
 161. **Figure 153**
 162. **Figure 154**
 163. **Figure 155**
 164. **Figure 156**
 165. **Figure 157**
 166. **Figure 158**
 167. **Figure 159**
 168. **Figure 160**
 169. **Figure 161**
 170. **Figure 162**
 171. **Figure 163**
 172. **Figure 164**
 173. **Figure 165**
 174. **Figure 166**
 175. **Figure 167**
 176. **Figure 168**
 177. **Figure 169**
 178. **Figure 170**
 179. **Figure 171**
 180. **Figure 172**
 181. **Figure 173**
 182. **Figure 174**
 183. **Figure 175**
 184. **Figure 176**
 185. **Figure 177**
 186. **Figure 178**
 187. **Figure 179**
 188. **Figure 180**
 189. **Figure 181**
 190. **Figure 182**
 191. **Figure 183**
 192. **Figure 184**
 193. **Figure 185**
 194. **Figure 186**
 195. **Figure 187**
 196. **Figure 188**
 197. **Figure 189**
 198. **Figure 190**
 199. **Figure 191**
 200. **Figure 192**
 201. **Figure 193**
 202. **Figure 194**
 203. **Figure 195**
 204. **Figure 196**
 205. **Figure 197**
 206. **Figure 198**
 207. **Figure 199**
 208. **Figure 200**
 209. **Figure 201**
 210. **Figure 202**
 211. **Figure 203**
 212. **Figure 204**
 213. **Figure 205**
 214. **Figure 206**
 215. **Figure 207**
 216. **Figure 208**
 217. **Figure 209**

Sketch of a water harvesting structure consisting of an earthen- or stone- built dyke that diverts water into cultivated fields. Several terraces are present in the fields in order to reduce slope gradient and retain water longer within the fields to allow maximum infiltration. Depending on the expected inflow of water several spillways can be made per terrace to prevent excessive concentration of flow in each spillway.

Technical knowledge required for field staff / advisors: moderate
(Selection of the proper location and assessment of up- and downstream linkages.)

Technical knowledge required for land users: low (Practical implementation of the water harvesting structure does not require a high level of knowledge)

Main technical functions: control of concentrated runoff: retain / trap, control of concentrated runoff: impede / retard, control of concentrated runoff: drain / divert, increase of infiltration, water harvesting / increase water supply

Secondary technical functions: increase of groundwater level / recharge of groundwater, water spreading

Spillway

Spacing between structures (m): 50

Depth of ditches/pits/dams (m): 0.5

Width of ditches/pits/dams (m): 1-3

Structural measure: water harvest dyke

Depth of ditches/pits/dams (m): <1

Width of ditches/pits/dams (m): <2

Length of ditches/pits/dams (m): <50

Construction material (earth): Soil from the stream banks is used to build the dyke and provide an opening into the cultivated field

Construction material (stone): Stones are used to fortify the dyke and spillways against the impact of flow.

Construction material (concrete): Potentially concrete is used to fortify the dyke and spillways against the impact of flow.

Specification of dams/ pans/ ponds: Capacity 5m³


Catchment area: >0.5km²

Beneficial area: 1-2 ha

Slope of dam wall inside: 100%;

Slope of dam wall outside: 100%

Dimensions of spillways: 1-3m wide and <50 cm deep



•
•
•
•
•

EURO

() 1 USD = 0.63 EURO

79.00

Labour costs and price of concrete are the most determinate factors affecting the costs.




1. Construction of a dyke (dam) (/ : summer or winter)

			(EURO)	(EURO)	%
Labour	5 meter dyke	1,0	150,0	150,0	100,0
Machine use	5 meter dyke	1,0	350,0	350,0	100,0

Concrete	5 meter dyke	1,0	400,0	400,0	100,0
				900.0	
				1'428.57	

1. restoration of the dyke (/ : once in 5 yr (after important events))


			(EURO)	(EURO)	%
Labour	5 meter dyke	1,0	4,0	4,0	100,0
Machine use	5 meter dyke	1,0	12,0	12,0	100,0
Concrete	5 meter dyke	1,0	25,0	25,0	100,0
				41.0	
				65.08	



[illegible]



Impact	Decreased	Increased	Notes
Improved crop yields			Depending on the amount of water harvested yield may be the same or increase slightly
			Implementation of dykes is considered relatively expensive
Improved livelihoods and human well-being			Water extraction by a water harvesting may cause less water at downstream locations, which may cause conflicts
			during Roman and Arab times when most structures were operative they increased significantly the production. Nowadays, most of them are abandoned. However, those that are operational do cause increased crop yields.
Reduced flood damage			For small flood events only
			Possibly a small effect

()
()



If various structures are present in a stream and only for relatively low intensity events

/





Implementation of the technology is relatively expensive. Once installed, maintenance is not expensive and pays off because of higher productivity.

()




()



1-10%
11-50%
> 50%

?



0-10%
11-50%
51-90%
91-100%

?



?



()

- The extra input of free water allows higher crop productivity.
- This technology is very effective at increasing water available for crop production and so increasing crop yield and farm income

How can they be sustained / enhanced? Temporarily store the harvested water in a cistern to be used for irrigation using drip irrigation when most needed.

- The technology takes advantage of floodwater that is otherwise lost because of the erratic character and short duration of flow

How can they be sustained / enhanced? Finding the optimal location for the water harvesting structures using a modelling approach

- Farmers consider it relatively expensive to implement and there is no guarantee for water as this depends on the rainfall events. Subsidies might help to install these structures where feasible. Therefore, good assessments of expected water inflow volumes are required before construction

- The implementation costs are relatively high when the bunds are made of concrete Use of cheap materials that are freely available (stones from the fields). However, it is important to make the structure as resistant as possible against flood events.
- The water provided by these techniques is mostly interesting for small- and medium- scale rainfed farming. Intensively irrigated farming requires more water and a guarantee for water independently of flood events Intensively irrigated farming might



Editors

Joris De Vente

Deborah Niggli
Alexandra Gavilano

: 1

2011

: 23

2019

Joris De Vente - SLM
Albert Solé Benet - SLM
Jorge López Carratala - SLM
Ascensión Ibáñez Torres - SLM
Antonio Escamez - SLM
- SLM

https://qcat.wocat.net/km/wocat/technologies/view/technologies_1517/

SLM

- Consejería de Agricultura y Agua Murcia (CARM) -
- EEZA-CSIC (EEZA-CSIC) -
- Book project: Water Harvesting – Guidelines to Good Practice (Water Harvesting)
- DESIRE (EU-DESIRE)

- rot, E., van Wesemael, B., Benet, A.S. and House, M.A., 2008. Water harvesting potential in function of hillslope characteristics: A case study from the Sierra de Gador Journal of Arid Environments 72(7):1213-1231: Internet
- Giráldez, J.V., Ayuso, J.L., García, A., López, J.G. and Roldán, J., 1988. Water harvesting strategies in the semiarid climate of southeastern Spain. Agricultural Water Management, 14(1-4): 253-263.: Internet
- Hooke, J.M. and Mant, J.M., 2002. Floodwater use and management strategies in valleys of southeast Spain. Land Degradation & Development, 13(2): 165-175.: Internet
- López-Gálvez, J. and Losada, A., 1998. EVOLUCIÓN DE TÉCNICAS DE RIEGO EN EL SUDESTE DE ESPAÑA. Ingeniería del Agua, 5(3): 41-50.: Internet
- Nasri, S., Albergel, J., Cudennec, C. and Berndtsson, R., 2004. Hydrological processes in macrocatchment water harvesting in the arid region of Tunisia: the traditional system of tabias. Hydrological Sciences-Journal, 49(2): 261-272.: Internet
- van Wesemael, B., et al., 1998. Collection and storage of runoff from hillslopes in a semi-arid environment: geomorphic and hydrologic aspects of the aljibe system in Almeria (Spain). Journal of Arid Environments 40(1):1-14: Internet
- Greenpeace, 2007. El negocio del agua en la cuenca del Segura, Greenpeace.: www.greenpeace.es

This work is licensed under [Creative Commons Attribution-NonCommercial-ShareAlike 4.0 International](https://creativecommons.org/licenses/by-nc-sa/4.0/)

